



GreaseShield 1850-ECO-S(Short) 5.107 EURO + (%16) K.D.V.

GS 1850 - ECO - S - PF
Stainless Stell Hygiene Stand
Additional Pre Filter Basket
Vortex Flow Controler



SIBA İTHALAT İHRACAT LTD.

Sht. Org. Eşref Bitlis Sok.
 No: 12 Alsancak / Girne
 Mersin 10 Turkey
 Tel: 822 4069 Fax-Tel: 822 4068

GreaseShield 1850-ECO-S(Short)

Functions & Features:

GS1850 ECO-S

PreFilter. As Standard for Solids Control. FilterShield Alternative Option.

Recirculation - Surface of water spray function to increase FOG removal and clean outlet weir area. Linked to cleaning LED.

Service Function - With Service Hose, Press and Hold button for 5 seconds to operate.

Vortex Flow Controller - Fitted as standard.

Running Trap - 54mm Running trap fitted on outlet as standard.

No Potable Water Connection

No CIP Bar

Other Parts Supplied as Standard

54mm 90° bend, 34mm 90° bend, 34mm End Cap, Key.

Default Program: (V1.0 ECO.)

Start 7.00 Am, Stop 02.30 Am.

FOG + Auger- Pulsing 5 Min On 5 min off .

Recirculation - 10 seconds on, every 90 seconds in each 5 min cycle.

Service Function - Manual button at the rear of machine is for service in conjunction with service grey hose.

Mains lead per country.

Installation Kit:

Stainless Steel 304 hygiene and service access adjustable stand essential for installation.

IP56 Socket.

Best Practice Management and Do's and Don'ts, both laminated to be displayed on site.

Daily Maintenance Logbook (12 months).

Plumbing Pack:

Water Spray gun and hose for connection to WRAS approved (or similar approval) connection (or equivalent) for service.

Sampling Point.

Spare filter basket.



Labelling:

Voltage per country.

Flow Rate per country.

Labels per country.

Labels per Distributor.

Average Power Consumption /Hour

16.0 Watts.

Notes:

All FlexiPlumb to be supplied with jubilee clip fasteners.

VFC= Vortex Flow Controller.



GreaseShield 1850-ECO-S(Short)



Environmental Products & Services Ltd.
www.EPAS-Ltd.com

